



- Notes:
- 1) Electrical connections and disconnected by others.
  - 2) Soft Start control panel included; Lockable. Remote mounted, NEMA 1 Enclosure, individual motor overload protection, ON/OFF keyed switch, Pre set 5-7 Second ramp up.
  - 3) Frames to be installed and supported individually.
  - 4) 4 Supports provided.
  - 5) Top intake standard, front intake available upon request.
- CSA Certified  
CWB Certified

**ENERSHIELD INDUSTRIES LTD**  
 18821-113 AVENUE  
 EDMONTON, ALBERTA T5M 2X2  
 PH (780) 482-4662 FAX (780) 482-4074  
 E-mail: info@enershield.ca  
 www.enershield.ca

Motors: 3 @ 20 hp IP55, TEFC, 1800RPM,  
 VFD Compatible  
 Available Voltages:  
 208-230/3/60, FLA 52-47, Total FLA 156-141  
 480/3/60, FLA 23.5, Total FLA 70.5  
 575/3/60 FLA 18.8, Total FLA 56.4

Xtremeshield	XS-390
Air Velocity (FPM) (M/S)	7500/38.1
Air Volume (CFM) (L/S)	77.43/236.544
Total hp/watts	60 hp/44.76kw
Weight lbs/kg	2740/1246

Project:	Tag:
Engineer:	Location:
Purchaser:	